

	Type	L #	Hits	Search Text	DBs
1	IS&R	L1	5410	(385/31,49,14,36).CCLS.	US-PGPUB; USPAT
2	BRS	L2	4632	(mirror or mirrored or reflector or reflective or deflector) with ("45" or "54.7" or "54.74" or "70.5" or "70.53") with (degree or degrees)	US-PGPUB; USPAT
3	BRS	L3	127	L1 and L2	US-PGPUB; USPAT
4	BRS	L4	41	L2 same (pyramidal or pyramidal)	US-PGPUB; USPAT
5	BRS	L5	166	L2 same (fiber or waveguide) same (pd or photodiode or photodetector or ld or laser or vcsl)	US-PGPUB; USPAT
6	BRS	L6	192	((mirror or mirrored or reflector or reflective or deflector) with (pyramid or pyramidal or triangular)) and "385"/\$.ccls.	US-PGPUB; USPAT
7	BRS	L7	2114	(mirror or mirrored or reflector or reflective or reflected or reflects or deflector) with (cantilever or cantilevered or ((bridge or suspended) adj2 waveguide))	US-PGPUB; USPAT
8	BRS	L8	154	L7 and "385"/\$.ccls.	US-PGPUB; USPAT
9	BRS	L9	632	L3 or L4 or L5 or L6 or L8	US-PGPUB; USPAT
10	BRS	L10	56	9 and @pd>"20050709"	US-PGPUB; USPAT

10/681019 (update)